	TRI-PARTY AG	GREEMENT	
Change Notice Number TPA-CN- 586	TPA CHANGE NO	TICE FORM	Date: 09/10/2013
Document Number, Title, and DOE/RL-2013-36 100-KR-4 Analysis Plan, Rev. 0	nd Revision: Groundwater Operable Unit Well II	nstallation Sampling an	Date Document Last Issued:
Originator: Jane V. Borghe	se		Phone: 373-3809
<b>Description of Change:</b> Table 4-1 Change Control is	s revised to give detail on analytical	method substitution an	
B.L. Charboneau	and <u>C. Guzzetti</u>		
DOE		EPA	agree that the proposed change
modifies an approved workp Section 9.0, <i>Documentation</i>	plan/document and will be processe and Records, and not Chapter 12.0	d in accordance with th ), Changes to the Agree	e Tri-Party Agreement Action Plan, ement.
Table 2-4 <i>Analytical Perforn</i> additional analytes.	nance Requirements for Water Sam	ples of DOE/RL-2013-3	6, Rev. 0 is revised to include
needed and deleted notificate performance requirements Change Notice, if appropriate requirements provided in second text is indicated in second text in seco	te) is needed when substituting an ection 2.2.2. etrikeout, added text is denoted by <u>d</u>	g analytical methods th L-2013-36, Rev. 0, and t analytical method that louble underline.	at meet or exceed analytical that a revision to the plan (or a TPA
	9, and 4-1 are affected by this chan	ge.	
Justification and Impacts of Table 2-4 revision states and	of Change: alytical requirements for constituer	nts identified in addend	a.
	ct that indicates analyte can be ana ents, clarifies that RL approval is rec		
Approvals:	1		
Briant Charbonean DOE Project Manager	Alley Sen	<u> </u>	Approved [] Disapproved
EPA Project Manager	,4	9/10/13 Date	Approved [] Disapproved
V N/	A		[] Approved [] Disapproved

Date

Ecology Project Manager

Table 2-4. Analytical Performance Requirements for Water Samples

Table 2 in Amarytour i Gromanico (Coquirements 10) water Gamples					
CAS	Analyte	Analytical Method <sup>a</sup>	EQL	Precision Requirement (%) <sup>b</sup>	Accuracy Requirement (%) <sup>b</sup>
		Performance Requirements fo	or Field Measuremer	ıts	
	Oxidation reduction potential	REDOX PROBE	N/A	c	c
	pH measurement	PROBE	0.5 pH unit	c	c
	Specific conductance	PROBE	1 μS/cm	c	c
	Temperature	PROBE		c	C
	Dissolved oxygen	PROBE		c	c
	Turbidity	PROBE	0.1 NTU	c	C
18540-29-9	Hexavalent chromium (screening)	EPA 7196 by HACH kit			, , , , , , , , , , , , , , , , , , ,
		Performance Requirements for Laborato	ory Measurements (I	Radiological)	
14762-75-5	Carbon-14	LSC - Carbon-14	5 pCi/L	±30	70-130
10098-97-2	Strontium-90	Strontium 89/90 – Sr-90	2 pCi/L	±30	70-130
10028-17-8	Tritium	LSC - Tritium (H-3)	400 pCi/L	±30	70-130
31.100		Performance Requirements for Laborator	y Measurements (No	onradiological)	
	Alkalinity	2320 Alkalinity	5,000 μg/L	<u>±20</u>	80-120
7440-36-0	Antimony	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	5 μg/L	±20	80-120
7440-38-2	Arsenic	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	2 μg/L <sup>d</sup>	±20	80-120
7440-39-3	Barium	EPA 6010 (ICP metal)	5 μg/L	±20	80-120
7440-41-7	Beryllium	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	2 μg/L	±20	80-120
	Bicarbonate	2320 Alkalinity	5,000 μg/L	<u>±20</u>	80-120

Table 2-4. Analytical Performance Requirements for Water Samples

Table 2-4. Analytical Ferromance Requirements for Water Samples					
CAS	Analyte	Analytical Method <sup>a</sup>	EQL	Precision Requirement (%) <sup>b</sup>	Accuracy Requirement (%) <sup>b</sup>
7440-43-9	Cadmium	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	2 μg/L <sup>d</sup>	±20	80-120
7440-70-2	<u>Calcium</u>	EPA 6010 (ICP metal)	<u>1,000 μg/L</u>	<u>±20</u>	80-120
	<u>Carbonate</u>	2320 Alkalinity	<u>5,000 μg/L</u>	<u>±20</u>	80-120
7440-47-3	Chromium	EPA 6010 (ICP metal)	10 μg/L	±20	80-120
7440-48-4	Cobalt	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	2.6 μg/L	±20	80-120
7440-50-8	Copper	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	8 μg/L	±20	80-120
18540-29-9	Hexavalent chromium	EPA 7196 <sup>d</sup>	10 μg/L	±20	80-120
7439-92-1	Lead	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	2 μg/L	±20	80-120
7439-95-4	<u>Magnesium</u>	EPA 6010 (ICP metal)	750 μg/L	<u>±20</u>	80-120
7439-96-5	Manganese	EPA 6010 (ICP metal)	5 μg/L	±20	80-120
7439-97-6	Mercury	EPA 7470 or 200.8	0.5 μg/L <sup>e</sup>	±20	80-120
7440-02-0	Nickel	EPA 6010 (ICP metal)	40 μg/L	±20	80-120
7440-09-7	<u>Potassium</u>	EPA 6010 (ICP metal)	<u>4,000 μg/L</u>	<u>±20</u>	80-120
7782-49-2	Selenium	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	4 μg/L	±20	80-120
7440-23-5	Sodium	EPA 6010 (ICP metal)	500 μg/L	<u>±20</u>	80-120
7440-28-0	Thallium	Trace – ICP (6010) or ICP/MS (6020 or 200.8)	2 μg/L <sup>e</sup>	±20	80-120
FARE	Total Carbonate	2320 Alkalinity	5,000 μg/L	<u>±20</u>	80-120
7440-61-1	Uranium	Total Uranium (chemical)	15 μg/L	±20	80-120
7440-62-2	Vanadium	EPA 6010 (ICP metal)	25 μg/L	±20	80-120

Table 2-4. Analytical Performance Requirements for Water Samples

CAS	Analyte	Analytical Method <sup>a</sup>	EQL	Precision Requirement (%) <sup>b</sup>	Accuracy Requirement (%) <sup>b</sup>
7440-66-6	Zinc	EPA 6010 (ICP metal)	10 μg/L	±20	80-120
75-35-4	1,1-Dichloroethene	EPA 8260 (VOCs)	2 μg/L <sup>e</sup>	±20	80-120
79-00-5	1,1,2-Trichloroethane	EPA 8260 (VOCs)	0.59 μg/L <sup>e</sup>	±20	80-120
71-43-2	Benzene	EPA 8260 (VOCs)	0.8 μg/L <sup>e</sup>	±20	80-120
56-23-5	Carbon tetrachloride	EPA 8260 (VOCs)	1 μg/L <sup>e</sup>	±20	80-120
67-66-3	Chloroform	EPA 8260 (VOCs)	5 μg/L	±20	80-120
79-01-6	Trichloroethene	EPA 8260 (VOCs)	1 μg/L <sup>e</sup>	±20	80-120
127-18-4	Tetrachloroethene	EPA 8260 (VOCs)	0.5 μg/L <sup>e</sup>	±20	80-120
75-01-4	Vinyl chloride	EPA 8260 (VOCs)	1 μg/L <sup>d</sup>	±20	80-120
16887-00-6	Chloride	EPA 300.0 (anions by IC)	400 μg/L	±20	80-120
16984-48-8	Fluoride	EPA 300.0 (anions by IC)	500 μg/L	±20	80-120
14797-55-8	Nitrate	EPA 300.0 (anions by IC)	250 μg/L	±20	80-120
14797-65-0	Nitrite	EPA 300.0 (anions by IC)	250 μg/L	±20	80-120
14808-79-8	Sulfate	EPA 300.0 (anions by IC)	550 μg/L	±20	80-120

Sources: 40 CFR 141.62, "National Primary Drinking Water Regulations," "Maximum Contaminant Levels for Inorganic Contaminants."

40 CFR 141.66, "National Primary Drinking Water Regulations," "Maximum Contaminant Levels for Radionuclides."

40 CFR 143.3, "National Secondary Drinking Water Regulations," "Secondary Maximum Contaminant Levels."

EPA, 2009, National Recommended Water Quality Criteria.

WAC 173-201A, "Water Quality Standards for Surface Waters of the State of Washington."

WAC 173-340-720, "Model Toxics Control Act—Cleanup," "Groundwater Cleanup Standards."

- c. Field measurements have no specific accuracy quality control requirement except to perform checks to verify manufacturer's expected performance.
- d. Hexavalent chromium analysis could be performed using a HACH® Test kit for screening purposes.

a. Equivalent methods may be substituted. For the three-digit EPA method, see EPA-600/4-79-020, *Methods for Chemical Analysis of Water and Wastes*. For the four-digit EPA methods, see SW-846, *Test Methods for Evaluating Solid Waste: Physical/Chemical Methods, Third Edition; Final Update IV-B*. Tentatively identified compounds will be reported for Method 8260 (SW-846).

b. Accuracy criteria for associated batch matrix spike percent recoveries. Evaluation based on statistical control of laboratory control samples also is performed. Precision criteria for batch laboratory replicate matrix spike analyses or replicate sample analyses.

Table 2-4. Analytical Performance Requirements for Water Samples

, and the second				··· <b></b>			
CA		Analyte	Analytical Method <sup>a</sup>	EQL	Precision Requirement (%) <sup>b</sup>	Accuracy Requirement (%) <sup>b</sup>	
e. Calci periodio	ulated cleaced cally reviews	anup goals are at or below esta ewed to establish if lower dete	ablished analytical methodology capabilitie ction limit capabilities have become availa	es. The analytical detection linble.	mits will be used for working l	evels and will be	
CAS		Chemical Abstracts Service	e	ICP = inductivel	y coupled plasma		
CCC	=	criterion continuous concentration		MS = mass spec	AS = mass spectrometry		
EQL	MARKET STATES	estimated quantitation limi	t	N/A = not applie	able		
GEA	William .	gamma energy analysis		NTU = nephelom	etric turbidity unit		
IC	100	ion chromatography	chromatography		rganic compound		

## 4 Change Management

Changes to this SAP and addenda will be reviewed and approved by DOE and the lead regulatory agency prior to implementation. Table 4-1 defines the types of changes that may be made to the documents.

A revision to this document may be necessary after a certain number (e.g., 5) of TPA (Ecology et al., 1989) change notices, at a major change in sampling, or at the request of the regulatory agency.

**Table 4-1. Change Control** 

Type of Change	Action	Documentation		
Adding constituents, or increasing sampling, or substituting an analytical method that meets or exceeds analytical performance requirements provided in section 2.2.2.	DOE-RL Project Manager approval; notify regulator.	Project's schedule tracking system		
Eliminating constituents, or wells, decreasing sampling, or a change in analytical method/quantitation limit to one that does not meet the analytical performance requirements provided in section 2.2.2.	Revise sampling and analysis plan (or TPA Change Notice, if appropriate); obtain DOE and regulatory approval; distribute plan.	Letter report documenting changes or revised plan (or approved TPA Change Notice)		
Well construction material or depth	DOE-RL Project Manager approval; notify regulator.	Project's schedule tracking system		
Well type	Revise sampling and analysis plan (or TPA Change Notice, if appropriate); obtain DOE and regulatory approval; distribute plan.	Letter report documenting changes or revised plan (or approved TPA Change Notice)		
DOE = U.S. Department of Energy				
DOE-RL = U.S. Department of Energy, Richland Operations Office				
TPA = Tri-Party Agreement (Ecology et al., 1989, Hanford Federal Facility Agreement and Consent Order)				